



Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to +40°C
Pulse rate and width:	Typical on time 20ms, off time 1.1-1.7sec (controlled by uC)
Pulse rate variation:	0.01%/volt, ±0.01% for temperatures -20°C to +40°C
Battery:	Lithium
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL SPECIFICATIONS									
Model	Battery	Battery Capacity (days)			Dimensions (mm)			Weight (grams)	Price Group
		35 ppm*	40 ppm	55 ppm	A	B	C		
A1220	2025	131	96	74	23	35	10	5.8	C
A1230	2032	175	129	99	23	35	11	6.5	C
A1240	2430	229	169	130	27	39	11	8.5	C
A1250	2354	445†	328	253	26	37	13	11.5	C
A1260	2477	796†	586	452	27	37	16	15.5	C

*15ms pulse width

†Factors other than battery capacity may reduce life.

Shown above right with optionally available Teflon ribbon.

Warranty life is 50% of battery capacity.

470 FIRST AVE NW · ISANTI, MN 55040
763.444.9267 · sales@atstrack.com · www.atstrack.com