



Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to +40°C
Pulse rate and width:	Typical on time 20ms, off time 1.1-2.0sec (controlled by astable circuit)
Pulse rate variation:	5%/volt, ±20% for temperatures 0°C to 40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL SPECIFICATIONS

Model	Battery	Battery Capacity (days)			Dimensions (mm)					Weight (grams)	Price Group
		30 ppm*	40 ppm	55 ppm	A	B	C	D	E		
A2410	379	34	20	14	7	18	3	4	9	1.0	A
A2420	377	58	34	25	8	19	4	4	9	1.3	A
A2430	392	94	55	40	9	20	5	4	9	1.7	A
A2440	394	164	96	70	11	22	5	4	9	2.0	A
A2450	393	158	93	68	9	20	7	4	9	2.2	A
A2460	389	198	116	85	13	24	5	4	9	2.6	A
A2470	386	257†	150	110	13	24	6	4	9	3.1	A
A2480	357H	441†	258	189	13	24	7	4	9	3.6	A

*15 ms pulse width.

†Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.