



Technical Specifications

Transmitter type:	Crystal controlled 2-stage ("B" suffix denotes 3-stage)
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to +40°C
Pulse rate and width:	Typical on time 20ms, off time 1100ms (controlled by uC)
Pulse rate variation:	0.01%/volt, ±0.01% for temperatures -20°C to +40°C
Battery:	Lithium
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL SPECIFICATIONS							
Model	Battery	Battery Capacity (days)		Dimensions (mm)		Weight (grams)	Price Group
		40 ppm	55 ppm	A	B		
	3.5V	40 ppm	55 ppm	A	B		
A2610*	10-12	73	56	12	32	8	E
A2620*	10-18	182	140	12	38	9	E
A2630*	10-25	264	202	12	45	11	E
A2650*	10-35	365	280	12	55	12	E
A2660	1/2AA	654	502	16	42	15	B
A2670	2/3AA	787	603	16	51	20	B
A2670B	2/3AA	300	400	16	51	22	B

*Flat bottom option

Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.

470 FIRST AVE NW · ISANTI, MN 55040
763.444.9267 · sales@atstrack.com · www.atstrack.com