



### Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to +40°C
Pulse rate and width:	Typical on time 20ms, off time 1100ms (controlled by astable circuit)
Pulse rate variation:	5%/volt, ±20% for temperatures 0°C to 40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

### MODEL SPECIFICATIONS

Model	Battery	Battery Capacity (days)			Dimensions (mm)		Weight† (grams)	Price Group
		30 ppm*	40 ppm	55 ppm	A	B		
A3340	394	164	96	70	11	10	2.2	B
A3370	386	257	150	110	13	10	3.3	B
A3380	357H	441	258	189	13	11	4.0	B

\*15ms pulse width.

†Weight given is for transmitter only. For total weight, add band and 0.5-1.5g of potting to attach band.

Band furnished by user.

Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.

470 FIRST AVE NW · ISANTI, MN 55040  
763.444.9267 · [sales@atstrack.com](mailto:sales@atstrack.com) · [www.atstrack.com](http://www.atstrack.com)