



Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to 40°C
Pulse rate and width:	Typical on time 20ms, off time 1.1-2.0sec (controlled by astable circuit)
Pulse rate variation:	5%/volt, ± 20% for temperatures -20°C to +40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL	BATTERY	BATTERY CAPACITY (days)			DIMENSIONS (mm)					WEIGHT (grams)	PRICE GROUP
		30 ppm*	40 ppm	55 ppm	A	B	C	D	E		
R1610	379	34	20	14	7	18	5	5	9	1.0	A
R1620	377	58	34	25	8	19	5	5	9	1.3	A
R1630	392	94	55	40	9	20	6	6	9	1.7	A
R1640	394	164	96	70	11	22	5	5	9	2.0	A
R1650	393	158	93	68	9	20	7	5	9	2.2	A
R1660	389	198	116	85	13	24	5	5	9	2.5	A
R1670	386	257 ⁺	150	110	13	24	6	5	9	3.1	A
R1680	357HC	441 ⁺	258	189	13	24	7	5	9	3.6	A

*15 ms pulse width

⁺Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.

470 First Ave. NW • Isanti, MN 55040
763.444.9267 • fax:763.444.9384 • sales@atstrack.com • www.atstrack.com