



Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to +40°C
Pulse rate and width:	Typical on time 15ms, off time 1.1-2.0sec (controlled by astable circuit)
Pulse rate variation:	5%/volt, ±20% for temperatures 0°C to 40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL SPECIFICATIONS

Model	Battery	Battery Capacity (days)			Dimensions (mm)					Weight (grams)	Price Group
		30 ppm*	40 ppm	55 ppm	A	B	C	D	E		
R1610	379	34	20	14	7	18	5	5	9	1.0	A
R1620	377	58	34	25	8	19	5	5	9	1.3	A
R1630	392	94	55	40	9	20	6	6	9	1.7	A
R1640	394	164	96	70	11	22	5	5	9	2.0	A
R1650	393	158	93	68	9	20	7	5	9	2.2	A
R1660	389	198	116	85	13	24	5	5	9	2.5	A
R1670	386	257†	150	110	13	24	6	5	9	3.1	A
R1680	357H	441†	258	189	13	24	7	5	9	3.6	A

*15 ms pulse width.

†Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.